

OPENET

GW-100

Multiservice Platforms



EMPOWERING RAPID DEPLOYMENT OF SERVICE INNOVATION

As a fixed, mobile or converged operator, you want to deliver revenue-generating, value-added services to both consumers and enterprises, more efficiently, securely and profitably. GW-100 is your single point of integration for network intelligence, policy control, traffic management, cyber threat protection and VAS, enabling delivery of high-level service innovation.

BENEFITS

- High performance: up to 500 Gbps in a single chassis; up to 4 Tbps in a chassis cluster
- Seamless, pay-as-you-grow scalability
- Real-time orchestration and traffic steering to value-added services hosted in or out of the chassis
- Superior DPI-based traffic classification enables granular policy and charging control
- Real-time collection of network usage data for any number of connected users and IoT devices

OPENET

© Copyright Openet Telecom, 2020

SINGLE POINT OF SERVICE INTEGRATION

GW-100 is an integrated platform for delivering innovative network services with exceptional quality of experience to any subscriber over any access and at any scale. Openet's growing portfolio of value-added services include:

- GW NetProtect (Security as a Service for consumers and businesses)
- GW URLfilter (regulatory URL filtering)

The platform also supports real-time traffic steering to third-party applications or virtualized services and enables seamless service chaining so your ability to craft differentiated service plans is practically unlimited. As a single point of integration for service delivery, GW-100 minimizes interoperability and integration issues to facilitate fast and efficient service rollout.

HIGH PERFORMANCE

With 100 Gigabit Ethernet connectivity and Terabits-per-second of throughput, GW-100 provides a platform for service providers to satisfy the ever-growing demand for innovative subscriber services and quality of experience.

FUTURE-PROOF SCALABILITY

Modular platform architecture lets you start small and expand up (connectivity, throughput) and out (capacity) seamlessly. Pay-as-you-grow deployment reduces initial capital outlay and allows operators to respond quickly to market changes.

- Capacity: supports up to 15 million active subscribers (concurrently attached and active), and 360 million concurrent IP flows
- Connectivity: up to 8 x 100GE ports or 96 x 10GE ports
- Throughput: up to 500 Gbps in a single platform
- Clustering: supports up to 8 GW-100 platforms in a seamless cluster configuration providing aggregate throughput of up to 4 Tbps
- Management: centrally configured and managed by GW Controller system, including full integration with GW SubscriberMgr

HIGH AVAILABILITY

The platform is compliant with NEBS Level 3 and provides 1+1 redundancy at the system level, and N+1 blade-level redundancy mechanisms to ensure service continuity with no downtime due to component failure.

ACCURATE TRAFFIC VISIBILITY AND POLICY CONTROL

Openet's traffic signature recognition technology, embedded in the platform, gives you granular visibility of application, user, device, quality-of-experience (QoE) and network topology traffic. Openet's extensive signature library accurately identifies hundreds of Internet applications and protocols, and also supports user-defined signatures. Frequent and automated updates to the signature library keep Openet Service Gateways up to date with the latest applications and Internet developments, ensuring accurate traffic detection and classification. Moreover, Openet's flexible and powerful Policy Editor makes it easy for you to provision and enforce real-time Quality of Service (QoS), steering, metering and charging policy with equal granularity.

ENCRYPTED TRAFFIC CLASSIFICATION

Openet's superior traffic classification proactively learns and adapts to the changing tactics of traffic encryption that is widely used by Internet services and data privacy applications. From heuristic analysis of IP flow behavior to peer learning and predictive DPI, Openet's synergy of inspection methods provides highly granular and accurate recognition of encrypted traffic even at maximum speeds and peak loads.

INTELLIGENT PCEF/TDF

Compliance with 3GPP standards and interoperability with most PCRF systems enables GW-100 to provide intelligent Traffic Detection Function (TDF) and Policy and Charging Enforcement Function (PCEF) in mobile data networks. As a result, network operators can leverage Openet's granular traffic classification and metering to enrich the policy decisions of PCRF elements, and to enhance the charging capabilities of online and offline charging systems (OCS, OFCS).

COLLECTING NETWORK DATA RECORDS

From its vantage point in the network, GW-100 collects and exports a rich variety of high-resolution usage data, including real-time transactions per user, per application, per device, per video session, per VoIP and Instant Messaging session, per Web session, and more. Network data records may be exported in standard formats to business intelligence systems, such as GW DataReporter, and other operator systems for further manipulation and analysis. Frequency and triggers for data record export are configurable parameters, giving operators ready access to usage data that is critical to their business. The data records coming from GW-100 are configurable and may be customized by Openet Data Science Services for any destination or use case requirements.

GW-100 PLATFORM

GW-100	
Platform Configuration	
Chassis	14-slot, AdvancedTCA (ATCA)
Maximum Available Slots	14
Core Controller (CC) Blade	1 to 12
Switch and Flow Balancer (SFB) Blade	1 to 4
Rear Input/Output (RIO) Blade	1 to 4
Service Blades	Up to 10
Capacity	
Throughput per Platform*	500 Gbps
Throughput per Cluster*	4 Terabits/sec using 8 devices
Number of Flows	360 Million (30 Million per Core Controller)
Number of Active Subscribers	15,000,000
Number of Lines / Pipes / Virtual Channels	512 / 4,800,000 / 24,000,000 (400,000 / 2,000,000 per Core Controller)
Interface Types	
Ethernet Interfaces	96 x 10 Gigabit Ethernet 8 x 100 Gigabit Ethernet
Management	2 x 1 Gigabit Ethernet or 2 x 10 Gigabit Ethernet (with 1:1 high availability)
Console	Serial, RJ45 Connector
Availability	
Hardware Bypass	Up to 4 independent, passive bypass units, supporting either 8 fiber-optic ports (4 links), or 16 fiber-optic ports (8 links), or 24 fiber-optic ports (12 links) per unit
High Availability	1+1 system-level redundancy N+1 redundancy of Core Controller blades
Management	Active-Standby HA on management ports
System	Redundancy for PSUs and fans
Dimensions	
Chassis Size	Standard 14U by 19" rack mount height 619.5mm (24.3"), width 444mm (17.48"), depth 433.04mm (17.04"), with PEMs
Chassis Weight	Up to 87.6 kg (193 lb)
AC Power Supply Size	External 1U by 19" rack mount, 445 x 43.6 x 401mm, 13.4kg (29.5lb)
Multi-Port Bypass Unit (8 ports)	External 1U 19" rack mount, LxWxH 439.5x130x43.6mm, 2.4kg (5.3lb)
HD-16 Multi-Port Bypass Unit	External 1U 19" rack mount LxWxH 439.5x145x43.6mm, 3kg (6.6lb)
HD-24 Multi-Port Bypass Unit	External 1U 19" rack mount LxWxH 439.5x145x43.6mm, 3kg (6.6lb)
Power Supply	
Input Voltage DC	-48V DC nominal (-40V to -60V DC)
Number of DC PSUs	2
DC Redundancy	1+1
Input Voltage AC	100 - 240V AC nominal (85V to 265V AC), 50/60Hz
AC Redundancy	2+2 @ 200V AC, 3+1 @ 100V AC, or N+N
Half Chassis Platform (2 SFB/RIO + 5 CC)	1660W

GW-100	
Power Consumption	
Full Chassis Platform (4 SFB/RIO + 10 CC)	2870W
Environment	
Operating Temperature	5 to 40°C (41 to 104°F)
Operating Temperature, short term	-5 to 55°C (23 to 131°F)
Storage Temperature	-40 to 70°C (-40 to 158°F)
Storage Relative Humidity	95%, non-condensing at temperatures of 23 to 40°C (73 to 104°F)
Operating Humidity, nominal	5 to 85% RH
Operating Humidity, short term	5 to 90% RH
Operating Altitude	60 to 1800m (-197 to 5906 ft) at 40°C Max 1801 to 4000m (5909 to 13123 ft) at 30°C
Standards	
NEBS	Designed to meet NEBS Level 3 Telecordia GR-1089-CORE, GR-63-CORE
CE Conformity	2004/108/EC Electromagnetic Compatibility Directive 2006/95/EC Low Voltage Equipment Directive 2011/65/EU RoHS Restriction of the use of certain hazardous substances 2002/96/EC WEEE Union's Wasted Electrical and Electronics Equipment Directive
Safety	EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 EN 60825-1:2007 EN 60825-2:2004 + A1:2007 + A2:2010 UL 60950-1:2007 R14.10 CAN/CSA-C22.2 No. 60950-07 + A1:2011 +A2:2014 UL94 CB/TUV
EMC	EN 55022:2010/AC:2011 EN 55024:2010 ETSI EN 300 386 V1.6.1:2012-04 for use in telecommunication canters EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6 FCC CFR 47 Part 15B Class A Industry Canada ICES-003 Issue 5; C108.8-M1983 Australia ACMA, AS/NZS CISPR 22:2009 + A1:2010 VCCI Class A Technical Requirements, V-3/2013.04
RoHS	EN 50581:2012
Quality System and Environment	Certified to standards ISO 9001, ISO/IEC 90003, ISO 14001, SI ISO 27001

GW-100 BLADES

SWITCH & FLOW BALANCER BLADES

		Switch & Flow Balancer SFB-400 Blade	Switch & Flow Balancer SFB-420 Blade
Capacity	Switching Capacity	720 Gbps	720 Gbps
	Flow Balancing Capacity	160 Gbps	540 Gbps
Interface Types	Console	Serial, RJ45 Connector	Serial, RJ45 Connector
Availability	Hot Swap	Supported	Supported
	Redundancy	1+1	1+1
Dimensions and Power	Size	Standard 1-slot ATCA blade	Standard 1-slot ATCA blade
	Weight	3.44 kg (7.7 lb)	5kg (11 lb)
	Power Dissipation (Max)	230W	250W
Standards	AdvancedTCA®	PICMG 3.0 R3.0	PICMG 3.0 R3.0

CORE CONTROLLER AND VAS BLADES

		Core Controller CC-400 Blade	NetworkSecure VAS WSP-500 Blade
Capacity	Throughput*	50 Gbps	120 Gbps in 3+1 Redundancy
	Number of Connections/Flows	15,000,000 / 30,000,000	N/A
	Pipes / Virtual Channels	400,000 / 2,000,000	N/A
	Number of Subscribers / PDP Contexts	1,500,000	N/A
Interface Types	Console	Serial, RJ45 Connector	Serial, RJ45 Connector
Availability	Hot Swap	Supported	Supported
	Redundancy	N+1	N+1
Dimensions and Power	Size	Standard 1-slot ATCA blade	Standard 1-slot ATCA blade
	Weight	3.44 kg (7.7 lb)	3.6 kg
	Power Dissipation (Max)	210W	295W (14 cores)
Standards	AdvancedTCA®	PICMG 3.0 R3.0	PICMG 3.0 R3.0

REAR I/O BLADES

	Rear Input/Output RIO-8C Blade	Rear Input/Output RIO-24C Blade	Rear Input/Output RIO-102CF Blade
Interface Types			
Ethernet Interfaces (Max per blade)	8 x 10GBASE-SR/LR/ER/ZR or 8 x 1000BASE-T/SX/LX/ZX and 12 x 10GBASE-SR/LR	24 x 10GBASE-SR/LR	2 x 100GBASE-SR4/LR4 4 x 10GBASE-SR/LR
Management	2 x 10GBASE-SR/LR or 2 x 1000BASE-T/SX/LX	2 x 10GBASE-SR/LR or 2 x 1000BASE-T/SX/LX	2 x 10GBASE-SR/LR or 2 x 1000BASE-T/SX/LX
Availability			
Hot Swap	Supported	Supported	Supported
Dimensions and Power			
Size	ATCA RTM blade	ATCA RTM blade	ATCA RTM blade
Weight	1.1 kg (3.3lb)	1.42 kg (3.1lb)	1.3 kg (2.9lb)
Power Dissipation (Max)	30W	40W	44W
Standards			
AdvancedTCA®	PICMG 3.0 R3.0	PICMG 3.0 R3.0	PICMG 3.0 R3.0
Supported SFB Blades			
Compatible with	SFB-400	SFB-420	SFB-420

* Actual throughput and performance metrics depend on enabled features, policy configuration, traffic mix, and other deployment characteristics.